

Rec'd PCT/PTO 08 SEP 2004

(19) World Intellectual Property Organization
International Bureau

10/506980

(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/075990 A2(51) International Patent Classification⁷: A61M 16/00(74) Agent: BONNEAU, Gerard; Cabinet Bonneau, Les Tais-
sounières HB3, 1681, route des Dolines, F-06560 Sophia
Antipolis (FR).

(21) International Application Number: PCT/IB03/01403

(22) International Filing Date: 10 March 2003 (10.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/362,441 8 March 2002 (08.03.2002) US(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(71) Applicant (*for all designated States except US*): KAERYYS
S.A. [FR/FR]; 50, Boulevard Stalingrad, F-06300 Nice
(FR).(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): DELACHE, Alain
[FR/FR]; 15, avenue de la Roseaie, F-06300 Nice (FR).
DELACHE, Véronique [FR/FR]; 15, avenue de la
Roseaie, F-06300 Nice (FR).

Published:

— without international search report and to be republished
upon receipt of that report

[Continued on next page]

(54) Title: AN AIR ASSISTANCE APPARATUS FOR COMPUTING THE AIRFLOW PROVIDED BY ONLY MEANS OF PRES-
SURE SENSORS

(57) Abstract: The invention concerns an apparatus (1) to assist a patient respiration by delivering air to a patient through a mask, said mask being designed to be connected on one first extremity of a tube, said apparatus comprising: - a control unit (2) to adjust the pressure delivered by the blower (4) of said apparatus, - a first pressure sensor (6) for sensing the pressure PM at said first tube extremity and being connected to said control unit, and - a second pressure sensor (8) for sensing the pressure PB at the air output of said blower and being connected to said control unit; in order that, when a tube is connected to said mask and connected to said apparatus on its said second extremity, the air flowing from the apparatus to the mask, said control unit is able to calculate the airflow at said second extremity of the tube from said pressures PM and PB and from the airflow resistance coefficient K_f of said tube.

WO 03/075990 A2